


NAIS

COMPACT POWER RELAY FOR INDUCTIVE LOAD

JM-RELAYS



- **Excellent contact welding resistance**
High contact pressure, a forced opening mechanism, and a forced wiping mechanism realizes an excellent contact welding resistance.

- **High breakdown voltage and surge resistant relay**
More than 6.4 mm .252 inch maintained for the insulation distance between contacts and coil, and the breakdown voltage between contacts and coil is 5,000 V for 1 minute. In addition, the surge resistance between contacts and coil is greater than 10,000 V.

- **Resistant to external force**
An absorber mechanism is used on the load terminals, giving a large improvement in characteristics variations caused by the external force during FASTON placement/removal.

- **Flux resistance mechanism**

The terminal area is plugged with resin to prevent flux seepage during PCB mounting. (TMP type)

- **Conforms to the various safety standards**

UL, CSA approved.
TÜV, VDE under application.

- **The line up can support economical mounting methods.**

The relay are equipped with a drive terminal (coil terminal) on one side for PCBs, and a load terminal (tab terminal #250) on the reverse side. The line up includes the TM type which can be attached directly to the PCB composing a drive circuit, and the TMP type which supports economical wiring. The TMP type can also be directly attached, and a high capacity load can be wired to the tab terminal.

Flat TMP type

mm inch

FEATURES

- **Compact, high-capacity, and resistant to inductive loads**

The relay is a compact 16×30.4×26.5 mm .630×1.197×1.043 inch. It can control an inductive load ($\cos\phi = 0.7$) with inrush current of 70 A and steady state current of 20 A.

SPECIFICATIONS

Contact

Arrangement		1 Form A		
Initial contact resistance, max. (By voltage drop 6 V DC 1 A)		100 mΩ		
Contact material		Silver alloy		
Rating (resistive load)	Nominal switching capacity		20 A 250 V AC	
	Max. switching power		5,000 VA	
	Max. switching voltage		250 V AC	
	Max. switching current		20 A	
Expected life (min. ope.)	Mechanical (at 180 cpm)		10 ⁶	
	Electrical Life (at 20 cpm)	Resistive load 20 A, 250 V AC ($\cos\phi = 1$)	10 ⁵	
			Inductive load	Inrush 70 A, Steady 20 A (250 V AC $\cos\phi = 0.7$)
		Inrush 80 A, Cut-off 80 A (When the motor is locked) (250 V AC $\cos\phi = 0.7$)		1.5×10 ³

Coil

Nominal operating power	900 mW
-------------------------	--------

Remarks


- * Specifications will vary with foreign standards certification ratings.
- *1 Measurement at same location as "Initial breakdown voltage" section
- *2 Detection current: 10mA
- *3 Wave is standard shock voltage of $\pm 1.2 \times 50\mu s$ according to JEC-212-1981
- *4 Excluding contact bounce time
- *5 Half-wave pulse of sine wave: 11ms; detection time: 10μs
- *6 Half-wave pulse of sine wave: 6ms
- *7 Detection time: 10μs
- *8 Refer to 5. Conditions for operation, transport and storage mentioned in AMBIENT ENVIRONMENT (Page 61).

Characteristics

Max. operating speed		180 cpm
Initial insulation resistance*1		Min. 100 MΩ (at 500 V DC)
Initial breakdown voltage*2	Between open contacts	1,000 Vrms for 1 min.
	Between contacts and coil	5,000 Vrms for 1 min.
Surge voltage between contact and coil*3		Min. 10,000 V
Operate time*4 (at nominal voltage)(at 20°C)		Max. 20ms (Approx. 8 ms)
Release time (without diode)*4 (at nominal voltage)(at 20°C)		Max. 10ms (Approx. 3 ms)
Temperature rise (at 60°C)		Max. 55°C (Contact switching current: 20 A/voltage applied to coil: 100%V)
Shock resistance	Functional*5	Min. 98 m/s ² {10 G}
	Destructive*6	Min. 980 m/s ² {100 G}
Vibration resistance	Functional*7	10 to 55 Hz at double amplitude of 1.6 mm
	Destructive	10 to 55 Hz at double amplitude of 2 mm
Conditions for operation, transport and storage*8 (Not freezing and condensing at low temperature)	Ambient temp.	-40°C to +60°C -40°F to +140°F
	Humidity	5 to 85% R.H.
Unit weight	Slim TMP	Approx. 28 g .99 oz
	Flat TMP	Approx. 32 g 1.13 oz
	Flat TM	Approx. 33 g 1.16 oz

TYPICAL APPLICATIONS ORDERING INFORMATION

- Compressor and heater control in air conditioners
- Power control in hot air type heaters
- Magnetron control in microwave ovens
- Lamp and motor control in OA equipment such as copiers and fac-similes.



Contact arrangement	Pickup voltage	Classification of type	Mounting classification	Coil voltage
1a: 1 Form A	N: 70% of nominal voltage	Nil: Slim type Z: Flat type	TMP: TMP type TM: TM type P: PCB type(Slim type)	DC 5, 6, 9, 12, 24, 48 V

(Notes) 1. Standard packing: Carton: 50pcs. Case: 200pcs.
 2. For Cd free contact material type, add suffix "-F".
 UL/CSA, VDE approved type is standard.




TYPES AND COIL DATA (at 20°C 68°F)

Part No.				Nominal voltage, V DC	Pick-up voltage	Drop-out voltage,	Nominal operating current, mA	Coil resistance, Ω (±10%)	Nominal operating power, mW	Max. allowable voltage, V DC
Slim		Flat								
TMP	PCB	TMP	TM							
JM1aN-TMP-DC5V	JM1aN-P-DC5V	JM1aN-ZTMP-DC5V	JM1aN-ZTM-DC5V	5	3.5	0.5	180	27.8	900	5.5
JM1aN-TMP-DC6V	JM1aN-P-DC6V	JM1aN-ZTMP-DC6V	JM1aN-ZTM-DC6V	6	4.2	0.6	150	40	900	6.6
JM1aN-TMP-DC9V	JM1aN-P-DC9V	JM1aN-ZTMP-DC9V	JM1aN-ZTM-DC9V	9	6.3	0.9	100	90	900	9.9
JM1aN-TMP-DC12V	JM1aN-P-DC12V	JM1aN-ZTMP-DC12V	JM1aN-ZTM-DC12V	12	8.4	1.2	75	160	900	13.2
JM1aN-TMP-DC24V	JM1aN-P-DC24V	JM1aN-ZTMP-DC24V	JM1aN-ZTM-DC24V	24	16.8	2.4	37.5	640	900	26.4
JM1aN-TMP-DC48V	JM1aN-P-DC48V	JM1aN-ZTMP-DC48V	JM1aN-ZTM-DC48V	48	33.6	4.8	18.75	2,560	900	52.8



DIMENSIONS

mm inch

Slim TMP type






PC board pattern (Copper-side view)





General tolerance: ±0.4 ±.016

Slim PCB type







PC board pattern (Copper-side view)



General tolerance: ±0.4 ±.016





Tolerance: ±0.1 ±.004



General tolerance: ±0.4 ±.016

Tolerance: ±0.1 ±.004

Flat TM type




General tolerance: ±0.4 ±.016

REFERENCE DATA


1. Coil temperature rise

Place to be measured: Inside of coil
Ambient temperature: 25°C 77°F




2. Ambient temperature characteristics

Sample: JM1aN-TMP-DC24V, 5 pcs.




3. Operate/release time

Sample: JM1aN-TMP-DC24V, 5 pcs.




4. Life curve




5-(1). 200 V AC electrical life test (200 V AC inverter dummy load)

Sample: JM1aN-TMP-DC12V, 6 pcs.
 Load: Inrush 108 A, Steady 15 A,
 Inverter dummy 200 V AC
 Switching frequency: ON 5 s, OFF 5 s
 Circuit




Change of pick-up and drop-out voltage

Contact welding: 0 time
 Miscontact: 0 time




5-(2). 100 V AC electrical life test (100 V AC inverter dummy load)

Sample: JM1aN-TMP-DC12V, 20 pcs.
 Load: Inrush 224 A, Steady 20A,
 Inverter dummy 100 V AC
 Switching frequency: ON 10 s, OFF 10 s
 Circuit




Change of pick-up and drop-out voltage

Contact welding: 0 time
 Miscontact: 0 time




5-(3). Inrush 70 A, Steady 20 A, 250 V AC compressor dummy load

Sample: JM1aN-TMP-DC12V, 6 pcs.
 Load: (Endurance) inrush 70 A $\cos\phi = 0.7$ (0.3 s), steady 20A $\text{pf} = 0.9$,
 250V AC compressor dummy
 (Overload) 80A $\cos\phi = 0.7$, 250 V AC
 No. of operations: (Endurance) 10^5 times
 (Overload) 1,000 times (after endurance test)
 Switching frequency: (Endurance) ON 1.5 s,
 OFF 1.5 s
 (Overload) ON 3 s,
 OFF 2 min., 57 s
 Circuit (endurance)



Change of pick-up and drop-out voltage

Contact welding: 0 time
 Miscontact: 0 time



For Cautions for Use, see Relay Technical Information (Page 48 to 76).