


**GLASS PASSIVATED
BRIDGE RECTIFIERS**
**REVERSE VOLTAGE - 50 to 1000 Volts
FORWARD CURRENT - 6.0 Amperes**
FEATURES

- Rating to 1000V PRV
- Ideal for printed circuit board
- Low forward voltage drop, high current capability
- Reliable low cost construction utilizing molded plastic technique results in inexpensive product
- The plastic material has UL flammability classification 94V-0



Dimensions in inches and (millimeters)

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Rating at 25°C ambient temperature unless otherwise specified.

Single phase, half wave, 60Hz, resistive or inductive load.

For capacitive load, derate current by 20%

CHARACTERISTICS	SYMBOL	GBJ 8A	GBJ 8B	GBJ 8D	GBJ 8G	GBJ 8J	GBJ 8K	GBJ 8M	UNIT
Maximum Recurrent Peak Reverse Voltage	V _{RRM}	50	100	200	400	600	800	1000	V
Maximum RMS Voltage	V _{RMS}	35	70	140	280	420	560	700	V
Maximum DC Blocking Voltage	V _{DC}	50	100	200	400	600	800	1000	V
Maximum Average Forward (with heatsink Note 2) Rectified Current @ T _J =100°C (without heatsink)	I(AV)				6.0				A
					2.8				
Peak Forward Surge Current 8.3ms single half sine-wave super imposed on rated load (JEDEC Method)	I _{FSM}				170				A
Maximum Forward Voltage at 4.0A DC	V _F				1.1				V
Maximum DC Reverse Current @ T _J = 25 °C at Rated DC Blocking Voltage @ T _J =125°C	I _R				5.0				uA
I ² t Rating for fusing (t<8.3ms)	I ² t				120				AS
Typical Junction Capacitance per element (Note 1)	C _J				55				pF
Typical Thermal Resistance (Note 2)	R _{th} C				1.8				°C/W
Operating Temperature Range	T _J				-55 to +150				°C
Storage Temperature Range	T _{STG}				-55 to +150				°C

NOTES: 1. Measured at 1.0MHz and applied reverse voltage of 4.0V DC.

2. Device mounted on 75mm x 75mm x 1.6mm Cu Plate Heatsink.